

BEAUMONT PRODUCTS, INC. 1560 BIG SHANTY DRIVE, KENNESAW, GA 30144
TELEPHONE 1-800-451-7096 1-770-514-9000 1-770-514-7400 FAX
In case of emergency please contact ChemTel: (800) 255-3924, Int'l (813)248-0585

SECTION 1 - Chemical Product & Company Identification

NAME: TREWAX Clear Paste Wax
Product Type: Paste Wax for Wood

| Health | Flammability | Reactivity | PPE |
|--------------------|------------------------|------------|-------------------------------------------|
| 1 | 2 | 0 | 0 |
| Health Hazard | Fire Hazard | Reactivity | Personal Protection |
| 0= minimal | 0= will not burn | 0= none | 0= not necessary |
| 1= slightly hazard | 1= FP>141F | 1= mild | 1= goggles |
| 2= hazardous | 2= FP=>73F=<141F | 2= strong | 2= goggles, gloves |
| 3= serious hazard | 3= FP<73F | | 3= goggles, gloves, protective clothes |
| 4= severe hazard | 4= BP<95F FP by TCC | | 4= goggles, gloves, & respirator |

*(DGIS)

SECTION 2 - Hazardous Ingredients

Petroleum Distillates CAS# 64742-47-8, 8052-41-3 Wt% = 67

SECTION 3 - Health Hazard & First Aid

1. Acute Health Effects: None
2. Chronic Health Effects: None
3. Carcinogen: No
4. Primary Entry Routes:
 - a) Skin & Eyes: Repeated contact with the skin may be irritating. Eye contact may be slightly irritating.
 - b) Ingestion: May be harmful.
 - c) Inhalation: Not considered a hazard.
5. First Aid:
 - a) Skin: Remove contaminated clothing-wash skin with soap and water. If irritation persists get medical attention.
 - b) Eyes: Wash eyes with large volumes of water for at least 15 minutes while lifting the upper and lower eyelids and rotating the eyeball. Get medical attention if irritation persists.
 - c) Ingestion: Give large volumes of water. Do not induce vomiting. Get medical attention.
 - d) Inhalation: N/A

SECTION 4 - Physical & Chemical Characteristics

| | |
|--------------------------------|---------------|
| 1. Physical State: | Paste |
| 2. Color: | Tan, Cream |
| 3. Odor: | Solvent |
| 4. Solubility in water: | Insoluble |
| 5. Specific Gravity (H2O=1.0): | .81 |
| 6. pH: | N/A |
| 7. Freezing Point: | N/A |
| 8. Flash Point: | 132 ° F (TCC) |
| 9. Vapor Pressure: | 0.5 |
| 10. VOC content: | 67% |

SECTION 5 - Fire and Explosion Hazard

- Flash Point: 132 °F (TCC)
- Extinguishing Media: Dry Chemical, Foam, CO₂
- Special Fire Fighting Procedures: Use water fog to cool containers to prevent from rupturing.
- Unusual Fire & Explosion Hazard: Fire fighters should observe all precautions that apply to any fire where chemicals are stored.

SECTION 6 - Reactivity Data

- Stability: Stable
- Conditions to Avoid: None Known

SECTION 7- Spill or Leak Procedures

- If product leaks or spills – Soak-up with Dry absorbent. Dispose in suitable container.
- Abide by Federal, State, and Local regulations.

SECTION 8 - Personal Protection

None Required

SECTION 9 - Special Precautions

- Store containers tightly closed and in an upright position.
- Do not destroy or deface the label.

SECTION 10 - Section 313 Supplier Notification (SARA)*

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372:
None

SECTION 11 - Toxicological Information

None

SECTION 12 - Ecological Information

None

SECTION 13 - Disposal Considerations

See Section 7 above.

SECTION 14 - DOT Transport Information

- This product is in Package Group II
- 2.2 lbs. containers and smaller are classed as CONSUMER COMMODITY ORM-D thus are exempt from regulation.
- Packages larger than 2.2 lbs. ARE regulated.
- The Bill of Lading

| <u>Proper Shipping Name</u> | <u>Class</u> | <u>ID</u> | <u>PG</u> | <u>Hazardous Material</u> |
|--------------------------------------------|--------------|-----------|-----------|---------------------------|
| Solids containing flammable liquid, n.o.s. | 4.1 | UN 3175 | II | “Petroleum Distillates” |

SECTION 15 - Other Regulatory Information

All ingredients appear on the TSCA Inventory List.

California Proposition 65: This material may contain the following components which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65.

Naphthalene: <0.00067%

New Jersey Right-to-Know Label

For New Jersey R-T-K labeling requirements, refer to components listed in Section 2.

SECTION 16 - Other Information

1. N/A = Not Applicable
2. *Dangerous Goods Identification System (DGIS)
3. TCC = Tag Closed Cup
4. Manufacturer believes that the information given here is accurate. The suggested procedures are based on experience and common sense and are not necessarily all-inclusive of every conceivable circumstance.